



AMERICAN FLAMECOAT INC.

520 Eagleton Downs Drive - D
Pineville, NC 28134
O: 704.405.2550
F: 704.543.9772
www.americanflamecoat.com

July 10, 2019

thesign / AG
NEUSEELAND 32
9404 RORSCHACHERBERG
SWITZERLAND

Reference: Flammability Test Report: 85761

One (1) fabric sample identified as Article **BAILEY 30695** (78%CV – 22%LI) treated with Flamecoat was received and tested in accordance with the California Technical Bulletin 117-2013, Section 1, Cover Fabric Test. The results are as follows:

<u>Test Results</u>		
Vertical Char Lengths		
11mm	11mm	12mm

The sample **meets** the requirements of the above standard. There were no ignitions or smoldering after 45 minutes on any of the three (3) specimens tested. In addition, none of the of the three test specimens displayed a char which was equal to or greater than 45mm.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brad Souffrant





AMERICAN FLAMECOAT INC.

520 Eagleton Downs Drive - D
Pineville, NC 28134
O: 704.405.2550
F: 704.543.9772
www.americanflamecoat.com

February 23, 2021

thesign / AG
NEUSEELAND 32
9404 RORSCHACHERBERG
SWITZERLAND

Reference: Laboratory Test Report
Lab Identification No. 95823

One (1) fabric sample, identified as **THE SIGN/AG – BAILEY 30695 – TREATED WITH FLAMECOAT**, was received and tested in accordance with **BRITISH STANDARDS 5852:2006, "Methods of Test for Assessment of the Ignitability of Upholstered Seating by Smouldering and Flaming Ignition Sources."** Per Section 14 a)1), "The following test results relate only to the ignitability of the combination of upholstery composites (BS 5852:2006, Clause 11) under the particular conditions of test stated; they are not intended as a means of assessing the full potential fire hazard of the materials or products in use."

The fabric sample submitted was tested to Section 9.3 (Crib Ignition Source 5) **using non-combustible foam**. The sample was tested after being subjected to BS 5852:2006, Annex E Water soaking and drying procedure. The results are as follows:

Ignition Source

Crib 5 #1 **PASS** (No flaming ignition or progressive smouldering ignition)
 #2 **PASS** (No flaming ignition or progressive smouldering ignition)

The fabric sample submitted **meets** the minimum requirements of the above standard when tested to crib ignition source 5 **using non-combustible foam**.

If there are any question, please let us know.

Brad Souffrant
President



Global FR, Fibercare Stain, Knit-backing, Increase double rubs & Anti-microbial treatment